



LOOKS LIKE REAL WOOD BUT PERFORMS BETTER, LASTS LONGER!

The hybrid, two-piece construction of Armourshake shingles adds to their dimension and profile. An extra-heavy fiberglass mat and modified sealant provide exceptional protection against Mother Nature's worst.

When installed with an approved underlayment, Armourshake shingles have a Class "A" Fire Resistance Rating – just one more important advantage over natural wood shakes.

Installation is easier, too, because IKO now offers a special accessory Armour Starter, designed to save installers time and labour. It's a flat strip embedded with granules that match the colours of the shingle, and it's placed beneath the cutouts. Not only does this facilitate installation, it further enhances the dimensional appearance of the shingles.



Ceramic-Coated Copper Granules
This provides an algae resistant layer of protection that won't break down in UV light.



- 1 Ceramic-Coated Granules**
Ceramic-coated granules, including colourfast Algae Resistant copper granules keep shingles looking beautiful for years - no more unsightly black streaks!
- 2 Oxidized Asphalt Coating**
Strong backbone of oxidized asphalt coating, to provide additional strength, weight, longevity and excellent handleability in hot weather applications.
- 3 Fibreglass Mat**
IKO's own Fibreteq heavyweight fibreglass mat provides a strong base for exceptional durability.
- 4 Backsurfacing**
Fine mineral backsurfacing for easy separation in the bundle.



Specifications	Standards†
Length 949 mm (37-3/8")	• ASTM D3462 • ASTM D3018
Width 470 mm (18-1/2")	• ASTM D3161 • ASTM E108 Class "A" Fire Resistance Rating††
Exposure 140 mm (5-1/2")	• CSA A123.5 • CSA A123.51
Coverage per Bundle 1.86 m ² (20 sq. ft.)	

Note: All values shown are approximate.

† Product is designed and tested to comply with ASTM/CSA Standards at time of manufacture prior to packaging.

Chalet Wood

Shadow Black

Greystone

Weathered Stone

Western Redwood

Notes: Shingle swatches shown are as accurate as modern printing processes allow. Shingle chips shown do not fully represent the entire color blend range of the shingles. To ensure complete satisfaction please make your final color selection from several full size shingles and view a sample of the product installed on a home.



Limited wind warranty coverage up to 230 km/h for ArmourShake
†† Use of an approved underlayment beneath all fiberglass shingles is strongly recommended especially on roof slopes below 6:12. Class "A" Fire Resistance Rating is achieved only with the installation of an approved underlayment.