

Extraordinary Dimensional Thickness

Cambridge LT laminated fiberglass asphalt shingles are the pinnacle of the Cambridge line, for performance and protection. Their extraordinary dimensional thickness creates a high-definition, natural “shake” look and profile. A double-layer construction of extra-heavy fiberglass mat combined with a tough modified sealant provides superior strength, durability, wind and weather-resistance. Cambridge LT carries a limited lifetime warranty.



Size: 1038 mm x 349 mm (40 7/8" x 13 3/4")
 Exposure: 149 mm (5 7/8")
 Quantity per pallet: 60 Bundles
 Coverage per package: 2.32 m² (25 sq. ft.)
 Shingles per square: 60

Warranty Term: Limited Lifetime Material
 Wind Resistance Warranty: Up to 210 km/h
 Fire Resistance Rating: Class A
 Iron Clad protection period: 10 years
 Cambridge LT: Algae Resistant Granules

Corresponding Products



The “HP” stands for “High Profile”, which means that they’re also designed to enhance the architectural shake-like appearance and dimensional profile of premium laminated fiberglass shingles.



ARMOURGARD Ice & Water Protector
 “Invisible” protection against roof leaks.” Helps prevent water leakage due to ice dams and wind-driven rain. Armourgard also creates a self-sealing bond around roofing nails.



Note: Shingle swatches shown are as accurate as modern printing processes allow. Shingle chips shown do not fully represent the entire color blend range of the shingles. To ensure complete satisfaction please make your final color selection from several full size shingles and view a sample of the product installed on a home.



Limited wind warranty coverage up to 210 km/h for Cambridge LT
 Note: Cambridge LT shingles available from Calgary and Sumas plants are designed with a straight cut.
 †† Use of an approved underlayment beneath all fiberglass shingles is strongly recommended especially on roof slopes below 6:12. Class ‘A’ Fire Resistance Rating is achieved only with the installation of an approved underlayment.